



---

**FOREMOST NODWELL 110 WITH 6-MAN CAB**  
**Hydrostatic Drive**



**6 Units Available**

| <b><u>Unit #</u></b> | <b><u>Hours</u></b> |
|----------------------|---------------------|
| 1                    | 2793                |
| 2                    | 3898                |
| 3                    | 4383                |
| 4                    | 1942                |
| 5                    | 2702                |
| 6                    | 2977                |

**DRIVE TRAIN**

---

|                     |  |
|---------------------|--|
| Engine:             | Cummins Diesel 6CTA 8.3C 250 HP @2500 RPM<br>Electric vernier throttle with preset high idle toggle<br>Spin-on fuel water separator<br>Additional fuel water separator<br>Ether/electric starting aid<br>Dry type two stage air cleaner<br>Thermatic fan |
| Track Pump:         | Rexroth AA 4V90 pumps  |
| Track Motors:       | Rexroth AA6VM200 motors  |
| Track Final Drives: | Rexroth L&S GFT56-T2 23.75:1 ratio<br>Ball valves to disconnect hydraulic drives for towing  |
| Drive Sprockets:    | Urethane drive sprockets<br>Sprockets in place of rubber front idler wheels  |
| Brakes:             | Service: Hydrostatic / dynamic braking<br>Parking: Internal disc brakes on Rexroth wheel ends  |

### **STEERING SYSTEM**

Hydrostatic with single lever joystick mounted onto seat armrest  
Joystick has automatic return to neutral feature  
Joystick is hydraulically operated (no cables)  
Track counter rotation capability

### **RUNNING GEAR**

|               |  |
|---------------|--|
| Tracks:       | Heavy duty track assembly 40 in. (1016mm) D-dent type, 1/2 in. x 4 in. (13mm x 102mm) grouser bars, 5/8 in. (16mm) bolts |
| Track Belt:   | PN200 - 6 ply  |
| Grouser Bars: | 1/2 in. x 3 in. (13mm x 76mm) spring steel   |
| Tires:        | 7:50 x 20 - 16 ply smooth crawler, urethane foam filled  |
| Suspension:   | Torsional coil spring<br>Cold weather springs, 5 in. (127mm) crank arms  |
| Hubs:         | 10 stud oil bath with metal face seals   |

### **CAB & ACCESSORIES**

V2000 Series 6 -man cab (102 inches wide) with engine doghouse  
All welded construction  
Steel lined with insulated walls, roof and floor  
Heated Westcoast type mirrors  
Escape hatch  
Slider door windows (four doors)  
Fixed rear window - safety glass

Windshield wipers  
 Bostrom Viking T-Bar driver's seat (nylon cloth covered)  
 Padded passenger (nylon cloth covered) seat c/w tool box  
 Rear passenger (nylon cloth covered) bench seat  
 Two sun visors  
 Dome light  
 Heavy duty style door stops  
 Tinted thermopane windshield  
 One seat belt  
 AM/FM radio and cassette deck

### **ELECTRICAL SYSTEM**

System: 12 volt  
 Alternator: 100 amp  
 Batteries: Delco 12 volt maintenance free  
 Headlights: 2 standard  
 Miscellaneous: Complete instrument control panel - illuminated (voltmeter, engine oil pressure, fuel, water temperature, tachometer/hourmeter)  
 Instruments for hydraulic temperatures and pressures  
 Engine monitor system (high temperature, low oil, low coolant)  
 Electric horns (2)  
 Fog lights (2)  
 Spotlight (cab mounted)  
 Rotating beacon  
 Backup alarm  
 Deck lights (2)  
 Air circulating fans (2)

### **HEATING & COOLING SYSTEM**

Arctic Pack: 100°F (38°C) ambient operating radiator assembly  
 Front shutters  
 Cab heaters and defrosters  
 Circulating block heater (electric 1500 watt, 110 volt)  
 Engine immersion block heater (electric 1000 watt, 110 volt)  
 Engine oil pan heater (electric 150 watt, 110 volt)  
 Hydraulic oil tank heater (150 watt, 110 volt)  
 Battery warmer (electric 110 volt)  
 Proheat 30,000 BTU diesel fueled engine coolant heater

### **AIR SYSTEM**

15 CFM compressor, tank, pressure gauge and Bendix AD9 air dryer  
 Alcohol injector

### **FRAME & DECK**

Frame: Welded frame of high strength steel  
 Full belly pans  
 Front and rear frame extensions

Deck: 12 ft. x 8 ft. (3.7 m x 2.4m) flat deck with stake pockets

Winch: Braden AHU7-16F 20,000 lb. (9080 kg.) capacity, cab controlled, hydraulically driven, front winch c/w 15/8 in. x 125 ft. (16mm x 38m) wire rope and tail chain

**TANKS**

Fuel/hydraulic tank  
Fuel - 27 US gal. (102 L)  
Hydraulic fluid - 45 US gal. (170 L)

**ACCESSORIES**

Lifting eyes  
Tow hooks (2 front)  
Front tow cable - 3/4 in. (19mm)

Please call for asking price and more details.

\*\*For more details please direct your inquiries to:

To: Mr. Jim Fulton  
Email: [jim\\_fulton@foremost.ca](mailto:jim_fulton@foremost.ca)  
Phone: 1-800-661-9190 ext: 805 (Canada/USA) or 1-403-295-5800 (Worldwide)